

**ITEM - ASPHALTIC CONCRETE (END PRODUCT) SHRP VOLUMETRIC MIX (\$)**

The Asphaltic Concrete shall be as specified in Sections 403 and 417 of the Standard Specifications, and Contracts and Specifications Stored Specs. "403ACHP" and "417SHRP."

The effective voids shall be  $\pm 0.2\%$ .

The ratio of the mix design composite gradation target for the No. 200 sieve, including admixture, to the effective asphalt content shall be a minimum of  $\pm$  to a maximum of 1.2.

The gyrations shall be Design  $\pm$ , Initial  $\pm$ , Max.  $\pm$ .

For estimating purposes the unit weight of the bituminous mix is  $\pm$  pounds per cubic foot and the asphalt cement is  $\pm\%$ .

The asphalt cement type shall be PG  $\pm$ .

*When either the Coarse Band or the Fine Band mix design grading limits are to be specified, the following must be included:*

The  $\pm$  band mix design grading limits shall be used.

The estimated haul distance for the asphaltic concrete is  $\pm\pm$  miles.

**DESIGNER:**

\$ List (1/2"), (3/4"), whichever is applicable.

\* To be supplied by the Bituminous Engineer.

\*\* To be supplied by the Geotechnical Site Supervisor.