

ITEM - ASPHALTIC CONCRETE (END PRODUCT) SHRP VOLUMETRIC MIX (\$) (With PG 76-22 TR+)

The Asphaltic Concrete shall be as specified in Section 417 of the Standard Specifications, and Contracts and Specifications Stored Spec. "417SHRP."

The effective voids shall be $_ * \pm 0.2 \%$.

The ratio of the mix design composite gradation target for the No. 200 sieve, including admixture, to the effective asphalt content shall be a minimum of $_ *$ to a maximum of 1.2.

The gyrations shall be Design $_ *$, Initial $_ *$, Max. $_ *$.

For estimating purposes the unit weight of the bituminous mix is $_ *$ pounds per cubic foot and the asphalt cement is $_ *$ %.

When either the Coarse Band or the Fine Band mix design grading limits are to be specified, the following must be included:

The $_ *$ band mix design grading limits shall be used.

The asphalt cement type shall be PG 76-22 TR+.

The estimated haul distance for the asphaltic concrete is $_ **$ miles.

DESIGNER:

Use this item when the average project elevation is less than or equal to 4,000 feet and the PG 76-22 TR+ binder is required.

\$ List (1/2"), (3/4"), whichever is applicable.

* To be supplied by the Bituminous Engineer.

** To be supplied by the Geotechnical Site Supervisor.