

## Evaluation Table

<b>PEP ID:</b>	XXXXX
<b>Manufacturer:</b>	Name of Manufacturer
<b>Product Name:</b>	Name of Product

705 Preformed Polymer Pavement Marking  
 705 Preformed Pavement Marking - Type II (Temporary, Removable)  
 ADOT Stored Specification: 705PVMRK, Sections 705-1(A), 705-1(C), 705-2.02  
 Responsible Section: Traffic Group

Material Property	Specification/ Test Method	Requirements	Results	Pass / Fail
Composition	705-2.02	Type II preformed pavement markings shall be a nonmetallic mixture of conformable materials and pigments intended for marking applications where removability is required.		
Color	705-2.02	The marking material shall be white or yellow retroreflective layer conforming to standard highway colors.		
Adhesive	705-2.02	The markings shall be precoated with a pressure sensitive adhesive capable of adhering to roadway surfaces under climatic and traffic conditions normally encountered in the construction work zone when applied in accordance with the manufacturer's instructions and without the use of heat, solvents or other additional adhesives.		
Exposure	705-2.02	Newly applied markings shall be capable of being immediately exposed to traffic without pickup or distortion by vehicles.		

Removal	705-2.02	Temporary pavement markings shall be removable from asphalt and concrete pavement intact or in large sections by following the manufacturer's instructions. It shall be removable, either manually or with a rollup device, at pavement temperatures above 40 degrees F without the use of heat, solvents, grinding or sand blasting. Visible adhesive residue remaining after removal of temporary pavement markings shall be easily removable without damaging or scarring the pavement surface and without the use of solvents or grinding.		
Thickness, inches, minimum	705-2.02	0.045		