

## Evaluation Table

<b>PEP ID:</b>	XXXXXX
<b>Manufacturer:</b>	Name of Manufacturer
<b>Product Name:</b>	Name of Product

800 Landscape Architectural Materials  
 808 Landscape Irrigation: Valves (Quick Coupling Valve)  
 ADOT Standard Specification: 808-2.01(C)  
 Responsible Section: Roadway Group

<b>Material Property</b>	<b>Specification/ Test Method</b>	<b>Requirement</b>	<b>Results</b>	<b>Pass/ Fail</b>
Quick Coupling Valve: General	808-2.01(C)	The quick coupling valve shall be bronze or brass with a 3/4-inch iron pipe size (I.P.S.) female inlet connection.		
Quick Coupling Valve: General	808-2.01(C)	The valve body shall be of two-piece construction with single slot and spring loaded self-closing valve with metal or rubber cover.		
Quick Coupling Valve: General	808-2.01(C)	All 3/4-inch quick coupling valves shall have a flow range of 10 to 20 gallons per minute and an operating pressure range of 5 to 125 pounds per square inch.		
Quick Coupling Valve: General	808-2.01(C)	All quick coupling valves shall be of a single manufacturer.		
Quick Coupling Valve: General	808-2.01(C)	Two quick coupling keys appropriate to the valve shall be provided for each 10 valves installed.		