



NOTES:

1. See M-1 for crosswalk and stop line details.
2. Refer to guidelines for turn lane design in ADOT Traffic Group Policies, Guides and Procedures.
3. Install post-mounted or overhead signing at the beginning of the turn lane in accordance with Chapter 2B of the MUTCD.
4. See project plans for pavement marker details.

Turn Lane Length (ft)	L ₁ (ft)	L ₂ (ft)	Supplemental Arrow	L ₃ (ft)
50-58	24-32	10	No	0
59-68	32	11-20	No	0
69-99	33-63	20	No	0
100-107	32	40	Yes	12-19
108-156	32-80	40	Yes	20
157-204	80	41-88	Yes	20
205-299	81-175	88	Yes	20
300+	176+	88	Yes*	20

* A second supplemental arrow may be placed equidistant between the arrow at the beginning of the turn and the ONLY legend.

DESIGN APPROVED	ARIZONA DEPARTMENT OF TRANSPORTATION INTERMODAL TRANSPORTATION DIVISION TRAFFIC SIGNING & MARKING STANDARD DRAWINGS	REVISION 6/14
SIGNATURES		DRAWING NO. M-11
APPROVED FOR DISTRIBUTION	TURN LANE PAVEMENT MARKINGS	SHEET NO. 1 of 1
ON FILE		

NOT TO SCALE