


Note to Designer: The information presented in this Standard Drawing has been prepared in accordance with recognized engineering principles and is for general use. It should not be used for specific application without competent professional examination and verification of its suitability and applicability by a licensed professional engineer. Contents within the inner border line shall not be altered.


04/19

PRIOR DISTRIBUTION DATE



For Foundation Details, see SD 9.10 (2 of 5)  
 For Foundation with barrier see SD 9.10 (5 of 5)

**TUBULAR CANTILEVER SIGN STRUCTURE ELEVATION**



TYPE	Post Height (Ft)	CAMBER		"A"
		"X"	"Y"	
1C	0-5	7/8"	1 5/8"	0° 20' 00"
	5.1-10	1"	2"	0° 24' 30"
	10.1-15	1 1/8"	2 1/4"	0° 29' 00"
2C	0-5	7/8"	1 1/2"	0° 18' 00"
	5.1-10	1"	1 3/4"	0° 22' 00"
	10.1-15	1 1/8"	2 1/8"	0° 26' 00"
3C	0-5	5/8"	1 1/8"	0° 13' 30"
	5.1-10	3/4"	1 3/8"	0° 16' 30"
	10.1-15	7/8"	1 5/8"	0° 20' 00"
4C	0-5	1 5/8"	3"	0° 25' 00"
	5.1-10	1 7/8"	3 1/2"	0° 30' 00"
	10.1-15	2 1/8"	4 1/8"	0° 35' 30"

**CAMBER NOTES:**

- The camber shown is required to be built into mast arm. Members shall be erected so that camber is provided above the horizontal line thru the field splice.
- The calculated camber provides for deflections due to dead loads of tubular cantilever structure and dead loads due to sign panels and attachments. For post heights between 0'-0" and 15'-0" values of "A", "X", and "Y" shall be interpolated.
- The pipe flange of mast arm shall be perpendicular to its longitudinal axis. The pipe flange of elbow shall be tilted from the vertical line at the angle given in the table.

TUBULAR CANTILEVER DATA FOR SIGN PANEL SUPPORT										PAYMENT ITEMS			
TUBULAR CANTILEVER				PIPE WALL THICKNESS ( INCHES)			SIGN PANEL						
Frame Type	Max Length	Max Height 'H'	Nominal Pipe Dia	Post	Elbow	Mast Arm	Max Area Sq. Ft.	Max Depth 'D'		CANTILEVER SIGN STRUCTURE		FOUNDATION	
									Item Number	Measurement	Item Number	Measurement	
1C	33'-0"	28'-0"	16"	1.219	1.219	0.500	92	12'	6060131	Ea	6060254	Ea	
2C	33'-0"	28'-0"	18"	1.156	1.156	0.625	151	12'	6060132	Ea	6060255	Ea	
3C	33'-0"	28'-0"	20"	1.280	1.280	0.625	245	12'	6060133	Ea	6060256	Ea	
4C	43'-0"	28'-0"	22"	1.125	1.125	0.875	186	10'	6060134	Ea	6060257	Ea	

**OVERHEAD SIGN NOTES:**

- Wind Loading: 90 MPH Velocity.
- Maximum Height: 50'-0" from average surrounding terrain to the center of the sign panel (Regardless of post height). The Tubular Cantilever has been designed for site conditions which are level and neither elevated above the average surrounding terrain by more than the 50'-0" height shown nor supported on a bridge.
- The maximum sign panel overlap onto elbow shall not exceed 7'-0" from field splice.
- The sum of the sign panel area plus the exit panel area shall not exceed the maximum area shown in the table. All signs shall be placed within Sign Panel Location.
- The Optional Shop Splice may not be used when the splice location is less than 5'-0" above the top of base plate. Shop splice of pipe sections (other than shown) are not permitted without prior approval.
- Drill and tap for 1 1/2" chase nipples and plug with recessed pipe plugs. Place perpendicular to sign panel axis and away from approaching traffic.
- If the tubular cantilever structure is erected as one unit, the pipe assembly shall be adequately suspended to avoid distortions.
- During sign erection the post shall be raked as necessary with the use of leveling nuts to make the sign panel level. See Traffic Signing Plans for specific locations and elevations.
- The Field Splice surfaces shall be in full contact without gaps prior to the bolts being snug tightened and fully tensioned. The contact surface is the area defined by a 1 3/8" radius around each bolt.
- Provide electrical grounding at pole foundations per ADOT Standard Specification Section 732-3.03.

**GENERAL NOTES:**

Construction Specification - Arizona Department of Transportation Standard Specifications for Road and Bridge Construction, latest Edition.

Design Specifications - AASHTO Standard Specification for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, 6th Edition (2013), including the 2015, 2019, and 2020 interim Revisions.

All tubular structural cantilever pipe shall be welded or seamless steel pipe and shall conform to ASTM Specification (Fy = 35,000 psi):

A-53	Grade B,	Type E or S
A252	Grade 2,	Type E or S
A106	Grade B,	Type S only
API 5L	Grade B,	Type E or S
API 5LX	Grade X42,	Type E or S

All other Structural Steel shall conform to ASTM Specification A36 unless noted otherwise.

All bolts shall conform to ASTM Specification F3125 GR A325.

All bolts, nuts and washers shall be galvanized in accordance with the requirements of ASTM A153. All other steel shall be galvanized after fabrication in accordance with ASTM A123.

Welding of structural tubing shall conform to the requirements of the American Welding Society, Structural Welding Code, D1.1, latest Edition.

All welding shall be continuous unless noted otherwise. All butt welds shall be full penetration using prequalified welding procedures and shall be tested by ultrasonic testing. All butt welds shall be ground flush, full width.

Grinding striations shall be parallel to the length of member.

The Column to base plate weld (WELD DETAIL A) and pipe flange to elbow and mast arm welds (WELD DETAIL C) shall be tested by ultrasonic testing. Any detected shallow toe cracks shall be repaired in the shop.

All Concrete shall be Class "S" (f'c = 3500 psi).

Reinforcing steel shall conform to ASTM Specification A615. All reinforcing shall be furnished as Grade 60.

All hooks and bends shall meet the requirements of AASHTO 8th Edition (2017) Article 5.10.2. All bend dimensions for reinforcing steel shall be out-to-out of bars. All placement dimensions for reinforcing steel shall be to center of bars unless noted otherwise.

Dimensions shall not be scaled from drawings.

Drilled shaft location and top of drilled shaft elevation shall be field verified by the Contractor prior to fabrication of post.

STANDARDS ENGINEER A. ALZUBI	ARIZONA DEPARTMENT OF TRANSPORTATION INFRASTRUCTURE DELIVERY AND OPERATIONS DIVISION <b>BRIDGE GROUP STANDARD DRAWING</b>	
RECOMMENDED FOR APPROVAL GROUP MANAGER D. BENTON	TUBULAR SIGN STRUCTURES TUBULAR CANTILEVER GENERAL PLAN	DRAWING NO. SD 9.10 (1 of 5)
APPROVED		
STANDARDS COMMITTEE APPROVED FOR DISTRIBUTION	11/22 DATE	

\*\* Payment for conduits and grounding wire is included in pay items 6060254, 6060255, 6060256, and 6060257 Foundation for Tubular Cantilever Sign Structure.

**HARDWARE NOTE:**

Provide 2 Hardened Steel washers, 2 Hex nuts and one Leveling nut for each bolt. At final position of post, all top and bottom nuts of anchor bolts shall be snug tightened against base plate

TABLE B		
Frame Type	Spiral Dia	Length L
1C	1/2"	6'-0"
2C	1/2"	6'-0"
3C	1/2"	6'-0"
4C	5/8"	10'-0"

(\*) Drilled shaft depth is based on uniform soils condition with unit weight = 110 pcf, friction angle phi = 29 degrees, modulus of subgrade reaction K=50 psf/ft. Depth or design of the drilled shaft shall be revised by the Engineer of Record for weaker soils or rock embedment, and all revision shall be shown on the project plans.

**GUSSET PLATE NOTES:**

Gusset plates shall be placed perpendicular to base plate and post face, and centered between anchor bolt holes.

Gusset Plate Details are shown on SD 9.10 (3 of 5).

**CONDUIT NOTE:**


If the project plans do not callout for the installation of a conduit, 2-1/2" diameter non-metallic conduits shall be stubbed out 30" below grade. The stubbed conduits shall be perpendicular to traffic direction to the non-traffic side, be a minimum of 12" from edge of foundation cap, and the conduit ends shall be capped.

**GROUNDING NOTES:**


A 25 feet long coil of No. 4 AWG bare copper grounding wire shall be installed before concrete is poured and shall be connected to the post grounding screw in the hand hole.

**GROUT NOTE:**

Space to be filled with non-shrink grout after tubular structure is permanently erected.



BASE PLATE DETAILS



ANCHOR PLATE DETAILS

**NOTES:**


All anchor bolts shall conform to ASTM F1554 Grade 55 Specifications. The upper 1'-2" and lower 6" shall be threaded. The upper 1'-8" shall be galvanized in accordance with the requirements of ASTM A153.

Provide bolt template during installation of anchor bolts. The bolt template shall be fabricated of 1/4" thick (Min) steel plate, similar to anchor plate details, and both the bolt template and the anchor plate shall be drilled to match the base plate.


Drilled shaft concrete shall be class 'S' and shall be placed within undisturbed material or compacted embankment. Top of drilled shaft shall be formed to 1'-0" below ground surface.

Compacted finished grade backfill or embankment shall be in place prior to erecting the post.

1/2" or 5/8" Spiral shall be cold drawn steel wire conforming to AASHTO M336, except Min Tensile Strength is 60,000 psi. Lap 1/2 turns at top and bottom of spiral.



ELEVATION



DRILLED SHAFT DETAILS

TABLE A	
Max Slope	'X'
8:1	0'
6:1	1'
4:1	2'
2:1	4'
1 1/2:1	5'
1:1	8'

Drilled Shaft Depth shall be adjusted for ground slope. Add value of 'X' in TABLE A to the minimum Drilled Shaft Depth to obtain the total length of shaft

Note to Designer: The information presented in this Standard Drawing has been prepared in accordance with recognized engineering principles and is for general use. It should not be used for specific application without competent professional examination and verification of its suitability and applicability by a licensed professional engineer. Contents within the inner border line shall not be altered.

03/22

PRIOR DISTRIBUTION DATE



STANDARDS ENGINEER A. ALZUBI	ARIZONA DEPARTMENT OF TRANSPORTATION INFRASTRUCTURE DELIVERY AND OPERATIONS DIVISION <b>BRIDGE GROUP STANDARD DRAWING</b>
RECOMMENDED FOR APPROVAL GROUP MANAGER D. BENTON	
APPROVED	TUBULAR SIGN STRUCTURES TUBULAR CANTILEVER FOUNDATION DETAILS
STANDARDS COMMITTEE APPROVED FOR DISTRIBUTION	DRAWING NO. SD 9.10 (2 of 5)

09/23  
DATE










Field Splice					
Frame Type	Pipe Dia	R Dia	R Thickness	No. of Bolts	B. C. Dia
1C	16"	22"	1/4"	22	19 1/2"
2C	18"	24"	3/8"	26	21 1/2"
3C	20"	26"	3/8"	29	23 1/2"
4C	22"	28"	1/2"	31	25 1/2"

**NOTE:**

Provide hand holes for TUBULAR CANTILEVER. See HAND HOLE & COVER DETAILS



3/4"  $\phi$  ATSM F3125 GR A325 bolts equally spaced. Bolt hole Dia = 13/16". Tighten bolts to a tension of 28K. All F3125 GR A325 bolts shall be installed in accordance with ADOT Standard Specification 604-2.03(c). See Field Splice Table for other details



\* Preheat per AWS requirements.


\*\* Stop Fillet Weld 1/2" from R ends

STANDARDS ENGINEER	A. ALZUBI
RECOMMENDED FOR APPROVAL	
GROUP MANAGER	D. BENTON
APPROVED	
STANDARDS COMMITTEE APPROVED FOR DISTRIBUTION	04/19 DATE


ARIZONA DEPARTMENT OF TRANSPORTATION INFRASTRUCTURE DELIVERY AND OPERATIONS DIVISION <b>BRIDGE GROUP STANDARD DRAWING</b>	
TUBULAR SIGN STRUCTURES TUBULAR CANTILEVER POST AND MAST ARM DETAILS	DRAWING NO. SD 9.10 (3 of 5)

Note to Designer: The information presented in this Standard Drawing has been prepared in accordance with recognized engineering principles and is for general use. It should not be used for specific application without competent professional examination and verification of its suitability and applicability by a licensed professional engineer. Contents within the inner border line shall not be altered.


PRIOR DISTRIBUTION DATE 03/11




PLAN  
SIGN MOUNTING BRACKET



ELEVATION  
SIGN MOUNTING BRACKET AT ELBOW




DETAIL D



ELEVATION C-C

Pipe Dia	Distance	
	'X'	'Y'
16"	6"	1'-8"
18"	7"	1'-10"
20"	8"	2'-0"
22"	9"	2'-2"



DETAIL E

\*\* Discontinue weld for 3 inches at shop splice location. See SD 9.10 (3 of 5)

STANDARDS ENGINEER  
A. ALZUBI  
RECOMMENDED FOR APPROVAL  
GROUP MANAGER  
D. BENTON  
APPROVED  
STANDARDS COMMITTEE APPROVED FOR DISTRIBUTION  
DATE 04/19

ARIZONA DEPARTMENT OF TRANSPORTATION  
INFRASTRUCTURE DELIVERY AND OPERATIONS DIVISION  
**BRIDGE GROUP STANDARD DRAWING**

TUBULAR SIGN STRUCTURES  
TUBULAR CANTILEVER  
SIGN SUPPORT DETAILS

DRAWING NO.  
SD 9.10  
(4 of 5)

Note to Designer: The information presented in this Standard Drawing has been prepared in accordance with recognized engineering principles and is for general use. It should not be used for specific application without competent professional examination and verification of its suitability and applicability by a licensed professional engineer. Contents within the inner border line shall not be altered.

PRIOR DISTRIBUTION DATE 03/11

