


NOTES:

- White and yellow delineators shall be used as guide markers to indicate roadway alignment. They shall always match the color of the edgeline and shall be placed as follows:
 - Double white delineators shall be used on the right side of right hand acceleration and deceleration lanes.
 - Double yellow delineators shall be used on the left side of left hand acceleration and deceleration lanes.
 - Single white delineators shall be placed on the right side of left-curving interchange ramps.
 - Single yellow delineators shall be placed on the left side of tangent and right-curving interchange ramps.
 - 360° white delineators shall be used on the right side of the throat area at the intersection of the crossroad and on-ramp. (See detail A)
 - 360° yellow delineators shall be used on the left side of the throat area at the intersection of the crossroad and on-ramp. (See detail A)
- Spacing shall be in accordance with the spacing table. Maximum ramp spacing shall be 200 ft.
- The crossroad through an interchange is normally delineated on the right side within the limits of the right-of-way at rural interchanges and grade separations. In urban areas or where sidewalks are present, crossroad and on-ramp throat delineation is not normally provided. Crossroad spacing shall conform to the table on Standard 4-M-4.02.
- For delineator details see Standard 4-M-4.01.



- Delineator Legend
- single white
 - ◇ double white
 - ⊙ 360° white
 - single yellow
 - ⊙ 360° yellow
 - triple horizontal object marker

Degree of curve	Spacing on curve in feet (s)	Spacing in advance and beyond curve in feet		
		A	B	C
0° 0' to 3° 00'	200	200	200	200
3° 01' to 6° 00'	150	200	200	200
6° 01' to 11° 00'	100	180	200	200
11° 01' to 18° 00'	75	135	200	200
18° 01' to 35° 00'	50	90	150	200
Greater than 35°	25	45	75	150

DESIGN APPROVED <i>Evelyn Brown</i> 7/10/81	STATE OF ARIZONA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS STANDARD DRAWINGS	REV. 8-81 7-86
APPROVED FOR DISTRIBUTION <i>James A. McRae</i> 8-24-80	INTERCHANGE DELINEATOR SPACING	DRAWING NO. 4-M-4.03