



R3-15a

HOV LANE ADVANCE (OVERHEAD)

A	B	C	D	E	F	G	H	J	K	L	M
84	48	0.625	0.75	5	6 D	3.5	6 D	3.5	3.5	11	3.5
12	72	0.75	1.25	8	8 D	6	8 E	6	5.5	16.5	6
144	84	0.75	1.25	8.5	10 D	8	10 E	8	7	16.5	6
156	108	.075	1.25	12	12 E	10	12 E	10.5	9.5	22	8

N	P	Q	R	S	T	U	V	W	X	Y	Z
15.011	4	6.303	2.585	3	19.728*	13.360	3.5	6 D	VAR	6	VAR
20.014	6	9.07	2.78	6	26.304	20.928	5	10 E	VAR	10	VAR
25.017	8	11.338	3.475	8	32.880	26.160	7	12 E	VAR	12	VAR
30.021	10	13.605	4.17	10	39.456	31.392	9	15 E	VAR	15	VAR

AA	BB	CC	DD	EE	FF	GG	HH	JJ
VAR	8	12	24	9.313	8.688	1.75	6	6
VAR	12	20	32	15.375	14.625	2.25	8	9
VAR	12	22	40	18.375	17.625	2.75	10	9
VAR	16	32	44	18.375	17.625	3.5	11	12

* Reduce character spacing 20%.

** See page 6-3 for arrow design.

LEFT SECTION

COLORS: LEGEND — WHITE (RETROREFLECTIVE)
BACKGROUND — BLACK

RIGHT SECTION

COLORS: LEGEND, BORDER — BLACK
BACKGROUND — WHITE (RETROREFLECTIVE)