



W1-5L

W1-5R
WINDING ROAD

*See page 6-2 for symbol design.

A	B	C	D	E	F	G	H	J	K	L	M
18	.375	.625	1	9.625	.375	2.5	.625	3	1	4	4
24	.375	.625	1.25	12.75	.5	3.25	.875	4.125	1.25	5.188	5.25
30	.5	.75	1.563	15.938	.625	4.063	1.094	5.156	1.563	6.484	9.563
36	.625	.875	1.875	19.125	.75	4.875	1.313	6.188	1.875	7.781	7.875
48	.75	1.25	2.5	25.5	1	6.5	1.75	8.25	2.5	10.375	10.5

N	P	Q	R	S
8.625	.25	2	1.25	1.5
11.375	.25	2.5	1.598	1.5
14.219	.313	3.125	2	1.875
17.063	.375	3.75	2.406	2.25
22.75	.5	5	3.188	3

COLORS: LEGEND – BLACK
BACKGROUND – YELLOW (RETROREFLECTIVE)

STANDARD ARROW DETAILS



A	B	C	D	E
2	2.313	4.063	.313	.375
2.25	2.625	4.5	.375	.438
2.5	2.875	5.063	.375	.5
2.625	3	5.25	.375	.5
2.75	3	5.563	.438	.563
3	3.5	6.125	.438	.563
3.125	3.625	6.375	.5	.625
3.25	3.75	6.625	.5	.625
3.313	3.813	6.688	.5	.688
3.5	4	7.125	.563	.688
3.75	4.313	7.625	.563	.75
4	4.625	8.125	.625	.813
4.063	4.75	8.25	.625	.813
4.25	4.875	8.625	.625	.813
4.375	5	8.875	.688	.875
4.5	5.188	9.125	.688	.875

A	B	C	D	E
4.75	5.438	9.625	.75	1
4.875	5.625	9.875	.75	1
5	5.75	10.125	.75	1
5.25	6	10.625	.813	1.063
5.5	6.375	11.125	.875	1.125
5.75	6.625	11.688	.875	1.125
6	6.875	12.188	.938	1.188
6.5	7.5	13.188	1	1.625
7	8	14.188	1.063	1.375
7.5	8.625	15.188	1.125	1.5
8	9.188	16.25	1.25	1.625